

View Online at <https://aerobasegroup.com/nsn/5340-00-089-5698>

Thread Class:

3b rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

0.850 inches and 0.910 inches rod connection

Shank Length:

Between 0.850 inches and 0.910 inches

Hole Diameter:

Between 0.1894 inches and 0.1899 inches

Shank Diameter:

Between 0.323 inches and 0.343 inches

Overall Height:

Between 0.615 inches and 0.635 inches

Overall Width:

0.875 inches

End Radius:

Between 0.280 inches and 0.340 inches

Fork Span Width:

Between 0.628 inches and 0.633 inches

Securing Pin Hole Diameter:

Between 0.052 inches and 0.072 inches

Distance From Center Of Securing Pin Hole To Rod End:

Between 0.280 inches and 0.340 inches

Distance From Pivot Pinhole Center To Rod Connection End:

Between 1.970 inches and 2.020 inches

Fork Arm Thickness:

Between 0.111 inches and 0.131 centimeters

Fork Depth:

Between 0.850 inches and 0.910 inches

Thread Size:

0.312 inches rod connection

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-268, cond t4 federal specification single material response

Surface Treatment:

Copper alloy

Surface Treatment Specification:

Mil-p-8585-canceled military specification single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A264a0

Mil-std (military Standard):

Mil-p-8585-canceled spec.