

View Online at <https://aerobasegroup.com/nsn/5340-00-097-6486>

Mounting Hole Type:

Threaded

First Leg Length:

0.281 inches

Second Leg Length:

0.375 inches

Second Leg Width:

0.469 inches

First Leg Hole Diameter:

Between 0.062 inches and 0.064 inches

Second Leg Hole Diameter:

0.086 inches

Second Leg Distance Between Hole Centers Along Width:

0.312 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.078 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.280 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

0.469 inches

First Leg Distance Between Hole Centers Along Width:

0.312 inches

First Leg Distance From Edge To Hole Center Along Width:

0.078 inches

First Leg Distance From Edge To Hole Center Along Length:

0.101 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Heat Treatment:

H-32 strain hardened

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.