

View Online at <https://aerobasegroup.com/nsn/5340-00-107-4261>

Fabrication Method (non-core):

Stamped

First Leg Length:

2.120 inches

Second Leg Length:

2.260 inches

Second Leg Width:

1.760 inches

First Leg Slot Length:

Between 0.880 inches and 0.910 inches

First Leg Slot Width:

Between 0.437 inches and 0.477 inches

Second Leg Hole Diameter:

Between 0.937 inches and 0.947 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.880 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.880 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

Center Section Height:

Between 2.780 inches and 2.840 inches

Center Section Width:

2.620 inches

Center Section Thickness:

0.250 inches

First Leg Width:

2.620 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 1.280 inches and 1.340 inches

First Leg Distance From Edge To Hole Center Along Length:

0.870 inches

Second Leg End Radius:

0.880 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

First leg tilted 40 degrees from x axis on z axis

Material:

Steel comp 1010 or steel comp 1025

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0