

View Online at <https://aerobasegroup.com/nsn/5340-00-109-4248>

First Leg Length:

1.750 inches

Second Leg Length:

3.000 inches

Reinforcement Method (non-core):

Raised center first leg

Second Leg Width:

6.750 inches

First Leg Slot Length:

0.750 inches

First Leg Slot Width:

0.531 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.875 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.062 inches

Second Leg Slot Length:

0.750 inches

Second Leg Slot Width:

0.531 inches

First Leg Thickness:

0.312 inches

Second Leg Thickness:

0.312 inches

First Leg Width:

6.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.875 inches

First Leg Distance From Edge To Hole Center Along Length:

0.625 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Heat Treatment:

O-annealed, recrystallized

Material:

Aluminum alloy 5083 or aluminum alloy 6061 or aluminum alloy 6062 or aluminum alloy 6061

Material Specification:

Qq-a-200/4 h112 federal specification 1st material response or qq-a-200/8 t6 federal specification 2nd material response or qq-a-200/8 t6 federal specification 2nd material response or qq-a-250/11 t6 federal specification 3rd material response

Surface Treatment:

Enamel

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0