

View Online at <https://aerobasegroup.com/nsn/5340-00-113-5644>

Mounting Hole Type:

Plain

First Leg Length:

1.560 inches

Second Leg Length:

0.880 inches

Reinforcement Method:

Gusset

Second Leg Width:

3.000 inches

Second Leg Corner Radius:

0.120 inches

First Leg Hole Diameter:

Between 0.220 inches and 0.680 inches

Second Leg Hole Diameter:

0.300 inches

Second Leg Distance Between Hole Centers Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Thickness:

0.060 inches

Second Leg Thickness:

0.060 inches

Center Section Height:

2.000 inches

Center Section Width:

3.000 inches

Center Section Thickness:

0.060 inches

First Leg Width:

3.000 inches

First Leg Corner Radius:

0.120 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.910 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

0.910 inches

First Leg Distance From Edge To Hole Center Along Width:

0.600 inches

First Leg Distance From Edge To Hole Center Along Length:

0.740 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Finish surface no. 5.1.1 or 5.2 plus 21.9 of mil-std-171, color white no27875

Material:

Steel

Material Specification:

Astma569 assn standard single material response

Surface Treatment:

Phosphate zinc

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.