

View Online at <https://aerobasegroup.com/nsn/5340-00-113-5644>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.560 inches

**Second Leg Length:**

0.880 inches

**Reinforcement Method:**

Gusset

**Second Leg Width:**

3.000 inches

**Second Leg Corner Radius:**

0.120 inches

**First Leg Hole Diameter:**

Between 0.220 inches and 0.680 inches

**Second Leg Hole Diameter:**

0.300 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.380 inches

**First Leg Thickness:**

0.060 inches

**Second Leg Thickness:**

0.060 inches

**Center Section Height:**

2.000 inches

**Center Section Width:**

3.000 inches

**Center Section Thickness:**

0.060 inches

**First Leg Width:**

3.000 inches

**First Leg Corner Radius:**

0.120 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

0.910 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

0.910 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.600 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.740 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Special Features:**

Finish surface no. 5.1.1 or 5.2 plus 21.9 of mil-std-171, color white no27875

**Material:**

Steel

**Material Specification:**

Astma569 assn standard single material response

**Surface Treatment:**

Phosphate zinc

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-std-171 spec.