

View Online at <https://aerobasegroup.com/nsn/5340-00-113-9334>

Fabrication Method:

Stamped and machined

Mounting Hole Type:

Countersunk and threaded

First Leg Length:

1.125 inches

Second Leg Length:

2.062 inches

Second Leg Width:

1.750 inches

First Leg Hole Diameter:

0.138 inches

Second Leg Hole Diameter:

0.156 inches

Second Leg Distance Between Hole Centers Along Width:

1.375 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.188 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.375 inches

First Leg Thickness:

0.062 inches

Second Leg Thickness:

0.062 inches

Center Section Height:

3.062 inches

Center Section Width:

1.750 inches

Center Section Thickness:

0.062 inches

First Leg Width:

1.750 inches

First Leg Distance Between Hole Centers Along Width:

1.375 inches

First Leg Distance From Edge To Hole Center Along Width:

0.275 inches

First Leg Distance From Edge To Hole Center Along Length:

1.375 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Heat Treatment:

Annealed

Material:

Stainless steel

Material Specification:

Qq-s-698 federal specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Style Designator:

Double angle

Test Data Document:

98230-ce93885 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0