

View Online at <https://aerobasegroup.com/nsn/5340-00-113-9334>

**Fabrication Method:**

Stamped and machined

**Mounting Hole Type:**

Countersunk and threaded

**First Leg Length:**

1.125 inches

**Second Leg Length:**

2.062 inches

**Second Leg Width:**

1.750 inches

**First Leg Hole Diameter:**

0.138 inches

**Second Leg Hole Diameter:**

0.156 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.375 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.188 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.375 inches

**First Leg Thickness:**

0.062 inches

**Second Leg Thickness:**

0.062 inches

**Center Section Height:**

3.062 inches

**Center Section Width:**

1.750 inches

**Center Section Thickness:**

0.062 inches

**First Leg Width:**

1.750 inches

**First Leg Distance Between Hole Centers Along Width:**

1.375 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.275 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.375 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Heat Treatment:**

Annealed

**Material:**

Stainless steel

**Material Specification:**

Qq-s-698 federal specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Style Designator:**

Double angle

**Test Data Document:**

98230-ce93885 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0