

View Online at <https://aerobasegroup.com/nsn/5340-00-116-4507>

First Leg Length:

1.550 inches

Second Leg Length:

1.550 inches

Second Leg Width:

Between 0.580 inches and 0.620 inches

First Leg Slot Length:

Between 0.420 inches and 0.460 inches

First Leg Slot Width:

Between 0.210 inches and 0.230 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.320 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.420 inches

Second Leg Slot Length:

Between 0.420 inches and 0.460 inches

Second Leg Slot Width:

Between 0.210 inches and 0.230 inches

First Leg Thickness:

Between 0.073 inches and 0.087 inches

Second Leg Thickness:

Between 0.073 inches and 0.087 inches

First Leg Width:

Between 0.580 inches and 0.620 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.320 inches

First Leg Distance From Edge To Hole Center Along Length:

0.420 inches

First Leg End Radius:

Between 0.480 inches and 0.520 inches

Second Leg End Radius:

Between 0.480 inches and 0.520 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One slot

First Leg Angle:

102.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0