

View Online at <https://aerobasegroup.com/nsn/5340-00-116-6322>

Fabrication Method (non-core):

Formed

First Leg Length:

0.633 inches

Second Leg Length:

0.960 inches

Second Leg End Width:

Between 0.560 inches and 0.640 inches

First Leg Slot Length:

Between 0.640 inches and 0.680 inches

First Leg Slot Width:

Between 0.210 inches and 0.230 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.320 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.430 inches and 0.460 inches

Second Leg Slot Length:

Between 0.420 inches and 0.460 inches

Second Leg Slot Width:

Between 0.210 inches and 0.230 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

Center Section Width:

1.080 inches

Center Section Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

1.080 inches

First Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.520 inches and 0.560 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.320 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

120.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0