

View Online at <https://aerobasegroup.com/nsn/5340-00-118-5045>

First Leg Length:

2.000 inches

Second Leg Length:

4.125 inches

Second Leg Width:

4.250 inches

First Leg Hole Diameter:

0.344 inches

Second Leg Hole Diameter:

0.094 inches

Second Leg Distance Between Hole Centers Along Width:

1.875 inches

Second Leg Distance Between Hole Centers Along Length:

3.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.119 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

2.000 inches

First Leg Corner Radius:

0.500 inches

First Leg Distance Between Hole Centers Along Width:

3.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

Second Leg Side Radius:

0.125 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Side radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

375.0 radians

Material:

Aluminum

Material Specification:

Aa319-t5 fscm 97403 mfr ref single material response

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-t-704 ty a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-t-704 spec.