

View Online at <https://aerobasegroup.com/nsn/5340-00-119-9162>

Fabrication Method (non-core):

Any acceptable

Mounting Hole Type:

Plain

First Leg Length:

0.813 inches

Second Leg Length:

0.750 inches

Second Leg Width:

2.438 inches

Second Leg Corner Radius:

0.062 inches

First Leg Hole Diameter:

0.149 inches

Second Leg Hole Diameter:

0.173 inches

Second Leg Distance Between Hole Centers Along Width:

1.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.375 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.062 inches

Second Leg Thickness:

0.062 inches

First Leg Width:

2.875 inches

First Leg Distance Between Hole Centers Along Width:

2.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.188 inches

First Leg Distance From Edge To Hole Center Along Length:

0.219 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

2 additional 0.203 in. Diameter holes in first leg

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.