

View Online at <https://aerobasegroup.com/nsn/5340-00-124-1844>

First Leg Length:

Between 0.720 inches and 0.780 inches

Second Leg Length:

Between 1.170 inches and 1.230 inches

Second Leg Width:

3.700 inches

First Leg Hole Diameter:

Between 0.208 inches and 0.214 inches

Second Leg Hole Diameter:

0.208 inches

Second Leg Distance Between Hole Centers Along Width:

Between 1.470 inches and 1.530 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 1.070 inches and 1.130 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.470 inches and 0.530 inches

First Leg Thickness:

Between 0.070 inches and 0.090 inches

Second Leg Thickness:

Between 0.070 inches and 0.090 inches

First Leg Width:

Between 3.670 inches and 3.730 inches

First Leg Distance Between Hole Centers Along Width:

Between 2.970 inches and 3.030 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.320 inches and 0.380 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.320 inches and 0.380 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

120.0 degrees

Heat Treatment:

T-3 solution heat treated

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, alclad t3 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

4001, fscm 97499 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0