

View Online at <https://aerobasegroup.com/nsn/5340-00-126-9112>

First Leg Length:

Between 0.580 inches and 0.650 inches

Second Leg Length:

Between 0.607 inches and 0.639 inches

Second Leg Width:

Between 0.430 inches and 0.450 inches

First Leg Hole Diameter:

Between 0.210 inches and 0.230 inches

Second Leg Hole Diameter:

Between 0.210 inches and 0.230 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.210 inches and 0.230 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.210 inches and 0.230 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

Center Section Height:

Between 0.357 inches and 0.389 inches

Center Section Width:

Between 0.430 inches and 0.450 inches

Center Section Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 0.430 inches and 0.450 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.210 inches and 0.230 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.210 inches and 0.230 inches

First Leg End Radius:

Between 0.320 inches and 0.440 inches

Second Leg End Radius:

Between 0.320 inches and 0.440 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Double angle

Fsc Application Data:

Engine, acft, turbo-prop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0