

View Online at <https://aerobasegroup.com/nsn/5340-00-127-3185>

**First Leg Length:**

Between 0.720 inches and 0.780 inches

**Second Leg Length:**

Between 1.170 inches and 1.230 inches

**Second Leg Width:**

Between 3.670 inches and 3.730 inches

**Second Leg Corner Radius:**

Between 0.470 inches and 0.530 inches

**First Leg Hole Diameter:**

Between 0.208 inches and 0.214 inches

**Second Leg Hole Diameter:**

Between 0.390 inches and 0.397 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 1.070 inches and 1.130 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.470 inches and 0.530 inches

**First Leg Thickness:**

0.080 inches

**Second Leg Thickness:**

0.080 inches

**First Leg Width:**

Between 3.670 inches and 3.730 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 2.970 inches and 3.030 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.320 inches and 0.380 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.320 inches and 0.380 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

120.5 degrees

**Heat Treatment:**

T-3 solution heat treated

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5, alclad t3 federal specification single material response

**Surface Treatment:**

Chromate zinc

**Surface Treatment Specification:**

Mil-a-6808 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-6808 spec.