## NSN 5340-00-127-3517

Swivel Caster - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-127-3517

## Center To Center Distance Between Bolt Holes Along Width:

Between 2.615 inches and 2.635 inches

## Center To Center Distance Between Bolt Holes Along Length:

Between 3.615 inches and 3.635 inches

## Wheel Quantity:

1

## Safe Operating Load Rating:

170.0 pounds

## Material And Location:

Rubber, soft tread

## Surface Treatment And Location:

Any acceptable

Unpackaged Unit Weight:

## 3.600 pounds

Wheel Type:

## Built up

Wheel Diameter:

4.000 inches

### **Effective Height:**

Between 5.188 inches and 5.312 inches

## Features Provided:

Axle lubrication fitting and swivel lubrication fitting and swivel lubrication fitting and electrically conductive

#### Plate Style:

Rectangular

#### Wheel Bearing Type:

Ball or roller

#### Swivel Bearing Type:

Ball or roller

#### Swivel Bearing Arrangement:

One row

#### Tread Width:

1.500 inches

#### Caster Plate Length:

4.688 inches

#### Caster Plate Width:

4.062 inches

#### **Caster Plate Mounting Hole Diameter:**

Between 0.380 inches and 0.400 inches

### Style Designator:

Swivel offset

#### Shelf Life:

N/a

# NSN 5340-00-127-3517

Swivel Caster - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A25600

