

View Online at <https://aerobasegroup.com/nsn/5340-00-127-4076>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 0.730 inches and 0.770 inches

Second Leg Length:

Between 2.352 inches and 2.400 inches

Reinforcement Method:

Turned edge

Second Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Hole Diameter:

Between 0.280 inches and 0.285 inches

Second Leg Hole Diameter:

Between 0.210 inches and 0.230 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.210 inches and 0.230 inches

First Leg Thickness:

Between 0.490 inches and 0.510 inches

Second Leg Thickness:

Between 0.032 inches and 0.040 inches

Center Section Height:

Between 0.900 inches and 1.000 inches

Center Section Width:

Between 0.490 inches and 0.510 inches

Center Section Thickness:

Between 0.032 inches and 0.040 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.210 inches and 0.230 inches

First Leg End Radius:

Between 0.350 inches and 0.390 inches

Second Leg End Radius:

Between 0.350 inches and 0.390 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Mounting pad on short leg

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0