

View Online at <https://aerobasegroup.com/nsn/5340-00-127-4076>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

Between 0.730 inches and 0.770 inches

**Second Leg Length:**

Between 2.352 inches and 2.400 inches

**Reinforcement Method:**

Turned edge

**Second Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Hole Diameter:**

Between 0.280 inches and 0.285 inches

**Second Leg Hole Diameter:**

Between 0.210 inches and 0.230 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.210 inches and 0.230 inches

**First Leg Thickness:**

Between 0.490 inches and 0.510 inches

**Second Leg Thickness:**

Between 0.032 inches and 0.040 inches

**Center Section Height:**

Between 0.900 inches and 1.000 inches

**Center Section Width:**

Between 0.490 inches and 0.510 inches

**Center Section Thickness:**

Between 0.032 inches and 0.040 inches

**First Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.210 inches and 0.230 inches

**First Leg End Radius:**

Between 0.350 inches and 0.390 inches

**Second Leg End Radius:**

Between 0.350 inches and 0.390 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Special Features:**

Mounting pad on short leg

**Material:**

Steel comp 321

**Material Specification:**

Ams 5510 assn standard single material response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0