NSN 5340-00-130-6043

Angle Bracket - Page 1 of 2





Mounting Hole Type: Threaded First Leg Length: Between 0.261 inches and 0.271 inches Second Leg Length: Between 0.307 inches and 0.317 inches Second Leg Width: Between 0.245 inches and 0.255 inches First Leg Hole Diameter: Between 0.081 inches and 0.091 inches Second Leg Hole Diameter: Between 0.091 inches and 0.101 inches Second Leg Distance From Edge To Hole Center Along Width: Between 0.120 inches and 0.130 inches Second Leg Distance From Edge To Hole Center Along Length: Between 0.083 inches and 0.103 inches **First Leg Thickness:** Between 0.055 inches and 0.065 inches Second Leg Thickness: Between 0.055 inches and 0.065 inches First Leg Width: Between 0.245 inches and 0.255 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.120 inches and 0.130 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.084 inches and 0.104 inches First Leg Style: Square First Leg Hole Arrangement Style: One hole Second Leg Style: Square Second Leg Hole Arrangement Style: One hole Second Leg Relationship To First Leg: Identical **First Leg Angle:** 90.0 degrees **Special Features:** Hole in 1st leg thd, no. 2-56 unc, class 2b **Heat Treatment:** T-6 solution heat treated

NSN 5340-00-130-6043

Angle Bracket - Page 2 of 2



Material:

Aluminum alloy 6061

Material Specification:

Qq-a-225/8, t6 federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0