## NSN 5340-00-131-1885

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-131-1885

First Leg Length:

Between 1.984 inches and 2.016 inches

Second Leg Length:

Between 2.734 inches and 2.766 inches

Second Leg Width:

2.434 mils and 2.516 centimeters

First Leg Slot Length:

0.438 inches

First Leg Slot Width:

0.219 inches

Second Leg Distance Between Hole Centers Along Width:

1.750 inches

**Second Leg Distance From Edge To Hole Center Along Length:** 

0.625 inches

Second Leg Slot Length:

0.438 inches

Second Leg Slot Width:

0.219 inches

First Leg Thickness:

Between 0.109 inches and 0.141 inches

**Second Leg Thickness:** 

Between 0.109 inches and 0.141 inches

First Leg Width:

Between 2.734 inches and 2.766 inches

First Leg Distance Between Hole Centers Along Width:

1.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.156 inches

First Leg Distance From Edge To Hole Center Along Length:

1.438 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

**Second Leg Hole Arrangement Style:** 

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

## **NSN 5340-00-131-1885** Angle Bracket - Page 2 of 2

Fiig: A042a0



| Special Features:   |
|---|
| One additional slot in first leg 0.219 in. Wide by 0.438 in. Lg |
| Material:   |
| Aluminum alloy 5052   |
| Material Specification:   |
| Qq-a-250/8 federal specification single material response       |
| Surface Treatment:  |
| Enamel  |
| Surface Treatment Specification:                                |
| 595 federal standard single treatment response                  |
| Style Designator:   |
| Angle   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |