

View Online at <https://aerobasegroup.com/nsn/5340-00-132-3257>

Fabrication Method (non-core):

Cast

Mounting Hole Type:

Plain

First Leg Length:

Between 0.670 inches and 0.690 inches

Second Leg Length:

Between 0.750 inches and 0.770 inches

Second Leg Width:

1.601 inches

First Leg Hole Diameter:

Between 0.201 inches and 0.207 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.233 inches

Second Leg Slot Length:

0.300 inches

Second Leg Slot Width:

0.206 inches

First Leg Thickness:

0.120 inches

Second Leg Thickness:

0.120 inches

First Leg Width:

1.600 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.320 inches

First Leg Distance From Edge To Hole Center Along Length:

0.430 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy a380.0

Material Specification:

Qq-a-591 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.