

View Online at <https://aerobasegroup.com/nsn/5340-00-134-3295>

First Leg Length:

0.563 inches

Second Leg Length:

1.250 inches

Second Leg Width:

0.750 inches

Second Leg End Width:

0.500 inches

First Leg Slot Length:

0.215 inches

First Leg Slot Width:

0.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.375 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.675 inches

Second Leg Slot Length:

Between 0.420 inches and 0.440 inches

Second Leg Slot Width:

Between 0.080 inches and 0.100 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

0.750 inches

First Leg Corner Radius:

0.187 inches

First Leg Distance Between Hole Centers Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Width:

0.187 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Two slotted holes 0.125 in. W, 0.215 in. Lg on 0.375 in. Center to center dim. In first leg

Material:

Steel comp 304

Material Specification:

Qq-s-766 federal specification single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 cl 4 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-13924 spec.