
NSN 5340-00-136-2212

Angle Bracket - Page 1 of 2



Fabrication Method (non-core): Any acceptable Mounting Hole Type: Plain First Leg Length: 2.000 inches Second Leg Length: 2.188 inches Second Leg Width: 4.000 inches First Leg Hole Diameter: Between 0.302 inches and 0.316 inches Second Leg Hole Diameter: Between 0.257 inches and 0.261 inches Second Leg Distance From Edge To Hole Center Along Width: 1.000 inches Second Leg Distance From Edge To Hole Center Along Length: 0.437 inches First Leg Thickness: 0.250 inches Second Leg Thickness: 0.250 inches First Leg Width: 4.000 inches First Leg Corner Radius: 0.062 inches First Leg Distance Between Hole Centers Along Width: 2.000 inches First Leg Distance From Edge To Hole Center Along Width: 1.000 inches First Leg Distance From Edge To Hole Center Along Length: 1.250 inches Second Leg End Radius: 0.437 inches First Leg Style: Corner radius First Leg Hole Arrangement Style: Two holes Second Leg Style: End radius and tapered Second Leg Hole Arrangement Style: One hole

NSN 5340-00-136-2212

Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-200/3 federal specification single material response

Surface Treatment:

Anodize

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0