

View Online at <https://aerobasegroup.com/nsn/5340-00-139-4993>

Fabrication Method (non-core):

Any acceptable

Mounting Hole Type:

Plain

First Leg Length:

Between 1.070 inches and 1.130 inches

Second Leg Length:

Between 1.220 inches and 1.280 inches

Second Leg Width:

Between 1.470 inches and 1.530 inches

First Leg Slot Length:

Between 0.390 inches and 0.450 inches

First Leg Slot Width:

Between 0.190 inches and 0.196 inches

Second Leg Hole Diameter:

Between 0.249 inches and 0.255 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.720 inches and 0.780 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.280 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

Between 1.470 inches and 1.530 inches

First Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.255 inches and 0.258 inches

First Leg Distance From Edge To Hole Center Along Length:

0.390 inches

Second Leg End Radius:

Between 0.220 inches and 0.280 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

105.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, alclad t3 federal specification single material response

Surface Treatment:

Chromate zinc

Surface Treatment Specification:

299-099-031 bell helicopter co. Mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0