

View Online at <https://aerobasegroup.com/nsn/5340-00-141-5741>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 0.380 inches and 0.420 inches

Second Leg Length:

Between 0.380 inches and 0.420 inches

Second Leg Width:

Between 0.600 inches and 0.640 inches

First Leg Hole Diameter:

Between 0.202 inches and 0.208 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

Center Section Height:

Between 0.420 inches and 0.440 inches

Center Section Width:

Between 0.600 inches and 0.640 inches

Center Section Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 0.600 inches and 0.640 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.300 inches and 0.320 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.185 inches and 0.195 inches

First Leg End Radius:

Between 0.480 inches and 0.520 inches

Second Leg End Radius:

Between 0.480 inches and 0.520 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

125.0 degrees

Second Leg Angle:

125.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Surface Treatment:

Passivate

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A042a0