

View Online at <https://aerobasegroup.com/nsn/5340-00-141-5741>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

Between 0.380 inches and 0.420 inches

**Second Leg Length:**

Between 0.380 inches and 0.420 inches

**Second Leg Width:**

Between 0.600 inches and 0.640 inches

**First Leg Hole Diameter:**

Between 0.202 inches and 0.208 inches

**First Leg Thickness:**

Between 0.056 inches and 0.068 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.068 inches

**Center Section Height:**

Between 0.420 inches and 0.440 inches

**Center Section Width:**

Between 0.600 inches and 0.640 inches

**Center Section Thickness:**

Between 0.056 inches and 0.068 inches

**First Leg Width:**

Between 0.600 inches and 0.640 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.300 inches and 0.320 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.185 inches and 0.195 inches

**First Leg End Radius:**

Between 0.480 inches and 0.520 inches

**Second Leg End Radius:**

Between 0.480 inches and 0.520 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

125.0 degrees

**Second Leg Angle:**

125.0 degrees

**Material:**

Steel comp 321

**Material Specification:**

Ams 5510 assn standard single material response

**Surface Treatment:**

Passivate

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A042a0