

View Online at <https://aerobasegroup.com/nsn/5340-00-146-5363>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

2.375 inches

**Second Leg Length:**

4.000 inches

**Second Leg Width:**

1.250 inches

**First Leg Hole Diameter:**

0.266 inches

**Second Leg Hole Diameter:**

0.438 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.625 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**Center Section Height:**

4.625 inches

**Center Section Width:**

1.250 inches

**Center Section Thickness:**

0.125 inches

**First Leg Width:**

1.250 inches

**First Leg Distance Between Hole Centers Along Length:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.625 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.625 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Special Features:**

Gloss yellow color

**Heat Treatment:**

H-32 strain hardened

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Oxide film or paint or primer

**Surface Treatment Specification:**

Mil-c-5541 military specification 1st treatment response or tt-p-1757 federal specification 2nd treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.