

View Online at <https://aerobasegroup.com/nsn/5340-00-146-5363>

Fabrication Method (non-core):

Machined

First Leg Length:

2.375 inches

Second Leg Length:

4.000 inches

Second Leg Width:

1.250 inches

First Leg Hole Diameter:

0.266 inches

Second Leg Hole Diameter:

0.438 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.625 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

4.625 inches

Center Section Width:

1.250 inches

Center Section Thickness:

0.125 inches

First Leg Width:

1.250 inches

First Leg Distance Between Hole Centers Along Length:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.625 inches

First Leg Distance From Edge To Hole Center Along Length:

0.625 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Gloss yellow color

Heat Treatment:

H-32 strain hardened

Material:

Aluminum alloy

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Oxide film or paint or primer

Surface Treatment Specification:

Mil-c-5541 military specification 1st treatment response or tt-p-1757 federal specification 2nd treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.