

View Online at <https://aerobasegroup.com/nsn/5340-00-147-9236>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.820 inches and 0.880 inches

Second Leg Width:

1.500 inches

First Leg Hole Diameter:

Between 0.274 inches and 0.288 inches

Second Leg Hole Diameter:

Between 0.585 inches and 0.601 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.510 inches

First Leg Thickness:

Between 0.087 inches and 0.093 inches

Second Leg Thickness:

Between 0.087 inches and 0.093 inches

First Leg Width:

1.500 inches

First Leg Corner Radius:

Between 0.230 inches and 0.270 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.990 inches and 1.010 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg End Radius:

Between 0.480 inches and 0.520 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Material:

Aluminum

Material Specification:

Ams4035 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1, class 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.