

View Online at <https://aerobasegroup.com/nsn/5340-00-147-9236>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.820 inches and 0.880 inches

**Second Leg Width:**

1.500 inches

**First Leg Hole Diameter:**

Between 0.274 inches and 0.288 inches

**Second Leg Hole Diameter:**

Between 0.585 inches and 0.601 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.510 inches

**First Leg Thickness:**

Between 0.087 inches and 0.093 inches

**Second Leg Thickness:**

Between 0.087 inches and 0.093 inches

**First Leg Width:**

1.500 inches

**First Leg Corner Radius:**

Between 0.230 inches and 0.270 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 0.990 inches and 1.010 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg End Radius:**

Between 0.480 inches and 0.520 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

One hole

**Material:**

Aluminum

**Material Specification:**

Ams4035 assn standard single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 1, class 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.