

View Online at <https://aerobasegroup.com/nsn/5340-00-148-1201>

**First Leg Length:**

1.140 inches

**Second Leg Length:**

1.410 inches

**Second Leg Width:**

4.386 inches

**Second Leg Corner Radius:**

0.250 inches

**First Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Distance Between Hole Centers Along Width:**

3.886 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.660 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

Between 0.056 inches and 0.062 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.062 inches

**First Leg Width:**

4.386 inches

**First Leg Corner Radius:**

0.531 inches

**First Leg Distance Between Hole Centers Along Width:**

2.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.470 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.800 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Second leg cutout 45 degrees 1.360 in. Deep

**Material:**

Titanium alloy

**Material Specification:**

Ams 4910 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0