

View Online at <https://aerobasegroup.com/nsn/5340-00-148-1218>

First Leg Length:

Between 0.729 inches and 0.771 inches

Second Leg Length:

Between 1.139 inches and 1.181 inches

Second Leg Width:

Between 1.506 inches and 1.516 inches

First Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Hole Diameter:

Between 0.199 inches and 0.207 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.234 inches and 0.266 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.234 inches and 0.266 inches

First Leg Thickness:

Between 0.045 inches and 0.055 inches

Second Leg Thickness:

Between 0.045 inches and 0.055 inches

First Leg Width:

2.010 inches

First Leg End Width:

1.510 inches

First Leg Distance Between Hole Centers Along Length:

Between 1.506 inches and 1.516 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.205 inches and 0.215 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.234 inches and 0.266 inches

Second Leg End Radius:

Between 0.234 inches and 0.266 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First leg radius on corners 0.234 in. Kmin, 0.266 in. Max

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0