

View Online at <https://aerobasegroup.com/nsn/5340-00-149-8544>

**First Leg Length:**

Between 0.880 inches and 0.920 inches

**Second Leg Length:**

Between 1.030 inches and 1.070 inches

**Second Leg Width:**

Between 0.485 inches and 0.515 inches

**First Leg Hole Diameter:**

Between 0.216 inches and 0.226 inches

**Second Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg Thickness:**

Between 0.056 inches and 0.062 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.062 inches

**First Leg Width:**

Between 0.485 inches and 0.515 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg End Radius:**

Between 0.344 inches and 0.406 inches

**Second Leg End Radius:**

Between 0.344 inches and 0.406 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

75.0 degrees

**Special Features:**

30.0 min, 38.0 max, rockwell c scale

**Material:**

Steel comp 410

**Material Specification:**

Ams 5504 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0