

View Online at <https://aerobasegroup.com/nsn/5340-00-149-8548>

First Leg Length:

Between 0.670 inches and 0.700 inches

Second Leg Length:

Between 1.801 inches and 1.831 inches

Second Leg Width:

Between 0.485 inches and 0.515 inches

First Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.344 inches and 0.406 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.344 inches and 0.406 inches

First Leg Thickness:

Between 0.056 inches and 0.062 inches

Second Leg Thickness:

Between 0.056 inches and 0.062 inches

First Leg Width:

2.010 inches

First Leg Corner Radius:

Between 0.234 inches and 0.266 inches

First Leg Distance Between Hole Centers Along Width:

1.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.234 inches and 0.266 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.234 inches and 0.266 inches

Second Leg End Radius:

Between 0.344 inches and 0.406 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Titanium alloy

Material Specification:

Ams 4910 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0