NSN 5340-00-150-2488

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-150-2488 **Fabrication Method (non-core):** Formed Second Leg Width: 0.500 inches **Second Leg Corner Radius:** 0.156 inches First Leg Hole Diameter: Between 0.307 inches and 0.317 inches Second Leg Hole Diameter: Between 0.216 inches and 0.226 inches Second Leg Distance From Edge To Hole Center Along Width: 0.250 inches First Leg Thickness: Between 0.056 inches and 0.062 inches Second Leg Thickness: Between 0.056 inches and 0.062 inches **Center Section Width:** 0.500 inches **Center Section Thickness:** Between 0.056 inches and 0.062 inches First Leg Width: 2.000 inches First Leg Corner Radius: 0.250 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: First Leg Distance From Edge To Hole Center Along Length: 0.250 inches First Leg Style: Corner radius First Leg Hole Arrangement Style: Two holes Second Leg Style: Corner radius **Second Leg Hole Arrangement Style:** One hole Material: Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

NSN 5340-00-150-2488

Double Angle Bracket - Page 2 of 2



Sty	16	u	=5	ıu	 aı	u	ч.	_

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0