

View Online at <https://aerobasegroup.com/nsn/5340-00-150-2496>

Fabrication Method (non-core):

Any acceptable

First Leg Length:

0.624 inches

Second Leg Length:

0.750 inches

Second Leg Width:

1.600 inches

First Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Hole Diameter:

Between 0.216 inches and 0.226 inches

Second Leg Distance Between Hole Centers Along Width:

1.100 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

Between 0.045 inches and 0.055 inches

Second Leg Thickness:

Between 0.045 inches and 0.055 inches

First Leg Width:

2.998 inches

First Leg Distance Between Hole Centers Along Width:

2.374 inches

First Leg Distance From Edge To Hole Center Along Width:

0.312 inches

First Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg End Radius:

0.312 inches

Second Leg End Radius:

0.250 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

32.0 min, 38.0 max, rockwell c scale

Material:

Steel comp 4130 or steel comp 8630

Material Specification:

Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0