

View Online at <https://aerobasegroup.com/nsn/5340-00-150-2497>

**First Leg Length:**

0.602 inches

**Second Leg Length:**

0.750 inches

**Second Leg Width:**

0.500 inches

**Second Leg Corner Radius:**

0.125 inches

**First Leg Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Second Leg Hole Diameter:**

Between 0.216 inches and 0.226 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

Between 0.045 inches and 0.055 inches

**Second Leg Thickness:**

Between 0.045 inches and 0.055 inches

**First Leg Width:**

3.000 inches

**First Leg Corner Radius:**

0.312 inches

**First Leg Distance Between Hole Centers Along Width:**

2.374 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.312 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.290 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

32.0 min, 38.0 max, rockwell c scale

**Material:**

Steel comp 4130

**Material Specification:**

Ams 6350 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0