NSN 5340-00-156-9764

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-156-9764

Cross Sectional Shape:
Circular recess
Inside Diameter:
0.937 inches
Hole Diameter:
0.203 inches
Width:
1.375 inches
Flange Thickness:
0.312 inches
Edge Shape:
Rectangle, multi holes
Length:
1.562 inches
Corner Radius:
0.187 inches
Hole Quantity Along Width:
4
Distance Between Holes Along Length:
1.140 inches
Distance Between Holes Along Width:
0.906 inches and 0.531 inches
Distance From First Hole Centerline To End Along Length:
Distance From First Hole Centerline To End Along Length: 0.313 inches
0.313 inches
0.313 inches Distance From First Hole Centerline To End Along Width:
0.313 inches Distance From First Hole Centerline To End Along Width: 0.422 inches
0.313 inches Distance From First Hole Centerline To End Along Width: 0.422 inches First Recess Inside Height:
0.313 inches Distance From First Hole Centerline To End Along Width: 0.422 inches First Recess Inside Height: 0.140 inches
0.313 inches Distance From First Hole Centerline To End Along Width: 0.422 inches First Recess Inside Height: 0.140 inches Inside Corner Radius:
0.313 inches Distance From First Hole Centerline To End Along Width: 0.422 inches First Recess Inside Height: 0.140 inches Inside Corner Radius: 0.187 inches
0.313 inches Distance From First Hole Centerline To End Along Width: 0.422 inches First Recess Inside Height: 0.140 inches Inside Corner Radius: 0.187 inches Body Thickness:
0.313 inches Distance From First Hole Centerline To End Along Width: 0.422 inches First Recess Inside Height: 0.140 inches Inside Corner Radius: 0.187 inches Body Thickness: 0.141 inches
0.313 inches Distance From First Hole Centerline To End Along Width: 0.422 inches First Recess Inside Height: 0.140 inches Inside Corner Radius: 0.187 inches Body Thickness: 0.141 inches Securing Device Type:
0.313 inches Distance From First Hole Centerline To End Along Width: 0.422 inches First Recess Inside Height: 0.140 inches Inside Corner Radius: 0.187 inches Body Thickness: 0.141 inches Securing Device Type: Threaded fastener
0.313 inches Distance From First Hole Centerline To End Along Width: 0.422 inches First Recess Inside Height: 0.140 inches Inside Corner Radius: 0.187 inches Body Thickness: 0.141 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
0.313 inches Distance From First Hole Centerline To End Along Width: 0.422 inches First Recess Inside Height: 0.140 inches Inside Corner Radius: 0.187 inches Body Thickness: 0.141 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole
0.313 inches Distance From First Hole Centerline To End Along Width: 0.422 inches First Recess Inside Height: 0.140 inches Inside Corner Radius: 0.187 inches Body Thickness: 0.141 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material:
Distance From First Hole Centerline To End Along Width: 0.422 inches First Recess Inside Height: 0.140 inches Inside Corner Radius: 0.187 inches Body Thickness: 0.141 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel

N/a

NSN 5340-00-156-9764 Access Cover - Page 2 of 2



			ure:	

Demilitarization:

No

Fiig:

A531c0