

View Online at <https://aerobasegroup.com/nsn/5340-00-158-5647>

Mounting Hole Type:

Plain and threaded

First Leg Length:

3.188 inches

Second Leg Length:

7.000 inches

Second Leg Width:

1.250 inches

Second Leg End Width:

6.000 inches

First Leg Hole Diameter:

Between 0.312 inches and 0.375 inches

Second Leg Hole Diameter:

0.312 inches

Second Leg Distance Between Upper Hole Centers Along Width:

3.843 inches

Second Leg Distance Between Hole Centers Along Length:

3.625 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

1.938 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.062 inches

Second Leg Distance From Edge To Hole Center Along Length:

3.000 inches

First Leg Thickness:

0.190 inches

Second Leg Thickness:

0.190 inches

First Leg Width:

1.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.562 inches

First Leg Distance From Edge To Hole Center Along Length:

0.688 inches

First Leg End Radius:

0.562 inches

Second Leg End Radius:

0.562 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020

Material Specification:

Astm a56 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0