

View Online at <https://aerobasegroup.com/nsn/5340-00-160-7969>

**First Leg Length:**

Between 0.850 inches and 0.870 inches

**Second Leg Length:**

0.920 inches

**Second Leg Width:**

Between 2.290 inches and 2.320 inches

**First Leg Hole Diameter:**

Between 0.185 inches and 0.200 inches

**Second Leg Hole Diameter:**

Between 0.220 inches and 0.235 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.750 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.265 inches and 0.285 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

Between 2.290 inches and 2.320 inches

**First Leg Distance Between Hole Centers Along Width:**

1.700 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.290 inches and 0.310 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

75.0 degrees

**Special Features:**

First and second leg corners chamfer

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/4, t4 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 1 military specification 1st treatment response or mil-a-8625, type 2 military specification 1st treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.