

View Online at <https://aerobasegroup.com/nsn/5340-00-160-7969>

First Leg Length:

Between 0.850 inches and 0.870 inches

Second Leg Length:

0.920 inches

Second Leg Width:

Between 2.290 inches and 2.320 inches

First Leg Hole Diameter:

Between 0.185 inches and 0.200 inches

Second Leg Hole Diameter:

Between 0.220 inches and 0.235 inches

Second Leg Distance Between Hole Centers Along Width:

1.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.265 inches and 0.285 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

Between 2.290 inches and 2.320 inches

First Leg Distance Between Hole Centers Along Width:

1.700 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.290 inches and 0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

75.0 degrees

Special Features:

First and second leg corners chamfer

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/4, t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification 1st treatment response or mil-a-8625, type 2 military specification 1st treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.