NSN 5340-00-161-1669

80205-nas1213 professional/industrial association standard

Webbing Strap - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5340-00-161-1669 |
|---|
| Width: |
| 1.000 inches |
| Length: |
| Between 14.500 inches and 15.500 inches |
| Environmental Protection: |
| Abrasion resistant and heat resistant and light resistant |
| End Type: |
| Both w/attachments |
| Ring Material: |
| Steel, mil-s-6758, comp 4130 |
| Buckle Material: |
| Steel, mil-s-6758, comp 4130 |
| Buckle Surface Treatment: |
| Cadmium, qq-p-416, type 2, class 3 |
| Buckle Location: |
| On end |
| Fastened Buckle Feature: |
| Included |
| Buckle Fastening Method: |
| Sewed |
| Ring Shape: |
| Delta shape swivel fitting w/short thread |
| Fastened Ring Feature: |
| Included |
| Ring Fastening Method: |
| Sewed |
| Ring Location: |
| On end |
| End Attachment/fastening Facility: |
| Ring and buckle |
| Buckle Style Designator: |
| Tie down |
| Color: |
| Natural |
| Material: |
| Nylon, mil-w-4088 or nylon, mil-w-27265, class r |
| Material: |
| Plastic polyhexamethylene adipamide or plastic polyhexamethylene adipamide |
| Material Specification: |
| Mil-w-4088 military specification 1st material response and mil-w-27265, class r military specification 2nd material response |
| Specification Data: |

NSN 5340-00-161-1669

Webbing Strap - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| T372-b | |

Mil-std (military Standard):

Mil-w-4088 spec.

Shelf Life: