

View Online at <https://aerobasegroup.com/nsn/5340-00-168-2773>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

6.380 inches

**Second Leg Length:**

10.315 inches

**Reinforcement Method (non-core):**

Gusset center section

**Second Leg Width:**

3.620 inches

**First Leg Hole Diameter:**

1.060 inches

**First Leg Slot Length:**

1.000 inches

**First Leg Slot Width:**

0.440 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.620 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**Second Leg Slot Length:**

1.000 inches

**Second Leg Slot Width:**

0.560 inches

**First Leg Thickness:**

0.375 inches

**Second Leg Thickness:**

0.375 inches

**First Leg Width:**

4.750 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

3.060 inches

**First Leg Distance Between Hole Centers Along Length:**

0.560 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Hole arrangement duplicated each leg first leg set 2.88 c-to-c second leg set 3.000 c-to-c

**Material:**

Steel comp 1015 or steel comp 1025

**Material Specification:**

Qq-s-631 federal specification 1st material response and qq-s-634 federal specification 2nd material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0