

View Online at <https://aerobasegroup.com/nsn/5340-00-168-2773>

Fabrication Method (non-core):

Stamped

First Leg Length:

6.380 inches

Second Leg Length:

10.315 inches

Reinforcement Method (non-core):

Gusset center section

Second Leg Width:

3.620 inches

First Leg Hole Diameter:

1.060 inches

First Leg Slot Length:

1.000 inches

First Leg Slot Width:

0.440 inches

Second Leg Distance Between Hole Centers Along Width:

2.620 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.000 inches

Second Leg Slot Length:

1.000 inches

Second Leg Slot Width:

0.560 inches

First Leg Thickness:

0.375 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

4.750 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

3.060 inches

First Leg Distance Between Hole Centers Along Length:

0.560 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Hole arrangement duplicated each leg first leg set 2.88 c-to-c second leg set 3.000 c-to-c

Material:

Steel comp 1015 or steel comp 1025

Material Specification:

Qq-s-631 federal specification 1st material response and qq-s-634 federal specification 2nd material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0