## NSN 5340-00-168-2802

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-168-2802

Fabrication Method (non-core):
Stamped
Mounting Hole Type:
Threaded
First Leg Length:
3.250 inches
Second Leg Length:
7.125 inches
Second Leg End Width:
6.000 inches
First Leg Hole Diameter:
Between 0.300 inches and 0.320 inches
Second Leg Hole Diameter:
Between 0.320 inches and 0.360 inches
Second Leg Distance Between Hole Centers Along Width:
5.120 inches
Second Leg Distance Between Hole Centers Along Length:
1.500 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.440 inches
Second Leg Distance From Edge To Hole Center Along Length:
2.000 inches
First Leg Thickness:
0.250 inches
Second Leg Thickness:
0.250 inches
Center Section Height:
4.500 inches
Center Section Width:
8.690 inches
Center Section Thickness:
2.500 inches
First Leg Width:
8.690 inches
First Leg End Width:
2.000 inches
First Leg Distance Between Hole Centers Along Width:
2.000 inches
First Leg Distance Between Hole Centers Along Length:
1.000 inches
First Leg Distance From Edge To Hole Center Along Width:

Between 0.970 inches and 1.030 inches

## NSN 5340-00-168-2802

Double Angle Bracket - Page 2 of 2



First Leg Distance From Edge To Hole Center Along Length:
0.370 inches
First Leg Style:
Square and tapered
First Leg Hole Arrangement Style:
Four holes
Second Leg Style:
Angle
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
45.0 degrees
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-250/11, 0 federal specification single material response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0