

View Online at <https://aerobasegroup.com/nsn/5340-00-168-6676>

Fabrication Method (non-core):

Any acceptable

First Leg Length:

4.000 inches

Second Leg Length:

4.000 inches

First Leg Slot Length:

0.620 inches

First Leg Slot Width:

0.281 inches

Second Leg Distance Between Hole Centers Along Width:

3.437 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

15.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.620 inches

First Leg Distance From Edge To Hole Center Along Length:

0.690 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Special Features:

A total of 20 slots, 10 in each half of bracket, 3.437 in. C to c

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.