

View Online at <https://aerobasegroup.com/nsn/5340-00-170-1691>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.630 inches

Second Leg Length:

1.000 inches

Second Leg Width:

0.500 inches

First Leg Hole Diameter:

Between 0.200 inches and 0.205 inches

Second Leg Hole Diameter:

0.098 inches

Second Leg Distance Between Hole Centers Along Length:

0.370 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

0.630 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.380 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

Second Leg End Radius:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Left hand offset

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, alclad t3 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.