

View Online at <https://aerobasegroup.com/nsn/5340-00-172-6912>

Fabrication Method (non-core):

Extruded

Mounting Hole Type:

Countersunk

First Leg Length:

0.281 inches

Second Leg Length:

0.281 inches

Second Leg Width:

0.438 inches

First Leg Hole Diameter:

0.070 inches

Second Leg Hole Diameter:

0.109 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.219 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.139 inches

First Leg Thickness:

0.046 inches

Second Leg Thickness:

0.062 inches

First Leg Width:

0.438 inches

First Leg Distance Between Hole Centers Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.094 inches

First Leg Distance From Edge To Hole Center Along Length:

0.094 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First leg corners chamfered 0.062 in. Lg by 45 deg, secondleg mtg hole plain

Heat Treatment:

T-4 solution heat treated

Material:

Aluminum alloy 2017

Material Specification:

Qq-a-225/5 t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 type 2 cl 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.