

View Online at <https://aerobasegroup.com/nsn/5340-00-172-6912>

**Fabrication Method (non-core):**

Extruded

**Mounting Hole Type:**

Countersunk

**First Leg Length:**

0.281 inches

**Second Leg Length:**

0.281 inches

**Second Leg Width:**

0.438 inches

**First Leg Hole Diameter:**

0.070 inches

**Second Leg Hole Diameter:**

0.109 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.219 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.139 inches

**First Leg Thickness:**

0.046 inches

**Second Leg Thickness:**

0.062 inches

**First Leg Width:**

0.438 inches

**First Leg Distance Between Hole Centers Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.094 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.094 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

First leg corners chamfered 0.062 in. Lg by 45 deg, secondleg mtg hole plain

**Heat Treatment:**

T-4 solution heat treated

**Material:**

Aluminum alloy 2017

**Material Specification:**

Qq-a-225/5 t4 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 type 2 cl 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.