

View Online at <https://aerobasegroup.com/nsn/5340-00-177-4029>

Thread Class:

3a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

0.865 inches rod connection and 0.885 inches rod connection

Shank Length:

2.938 inches

Hole Diameter:

Between 0.583 inches and 0.603 inches

Shank Diameter:

Between 0.302 inches and 0.322 inches

Overall Height:

Between 0.458 inches and 0.478 inches

Overall Width:

Between 0.585 inches and 0.615 inches

End Radius:

0.234 inches

Metallic Hardness Rating:

39.0 rockwell c and 45.0 rockwell c

Fork Span Width:

Between 0.471 inches and 0.481 inches

Distance From Pivot Pinhole Center To Rod Connection End:

3.620 inches

Fork Arm Thickness:

Between 0.057 inches and 0.067 centimeters

Fork Depth:

Between 0.910 inches and 0.970 inches

Thread Size:

0.312 inches rod connection

Special Features:

Additional pivot pin hole diameter 0.250 in. Min., 0.252 in. Max.

Material:

Steel comp 630

Material Specification:

Ams 5643 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A264a0